

Percent Oxygen Transmitter



Product shown with optional flow meter, needle valve, and coalescing filter

FEATURES	BENEFITS
Wide Number of Ranges	Measure from <0.1% to 100% Oxygen
Exceptional Speed of Response	Responds Instantaneously to Changes in Oxygen
Rugged and Versatile Construction	NEMA 4 Housing Withstands Harsh Environments
Economically Priced	Save Thousands of Dollars vs Other Methods
Extended Life Sensor	Eliminates Frequent Sensor Replacement
Acid Gas Resistant Sensor	Eliminates Sample Conditioning for Many Applications

Product Description

The Series 2500 Trace Oxygen Transmitter is a true loop powered (14-32 VDC) percent oxygen transmitter designed to provide accurate and dependable percent oxygen measurements in a variety of background gases. Measurement ranges available are from 0-2% to 0-100%. The Series 2500 enclosure is made from durable polycarbonate, and is rated for NEMA 4 (IP 66) service (may change with the addition of certain optional equipment). A 4-20 mA DC output is provided that can be used with a data logger, recorder, PLC, DCS, etc. Options include pressure regulators, flow meters, sample filters, and explosion proof (NEMA 7) housings.

The Series 2510 Percent Oxygen Transmitter is the AC powered (115/230 VAC, 50-60 Hz) counterpart to the Series 2500 and is recommended when AC power is available or preferred.

In addition to the optional equipment mentioned above, the Series 2510 can be equipped with sample pumps, sensor heaters, solenoid valves, loss of sample flow signal indication. A 4-20 mA DC analog output is provided.

The Series 2500 and Series 2510 Percent Oxygen Transmitters feature an extended life oxygen sensor with EES (enhanced electrolyte system). This sensor provides exceptional performance, accuracy, and stability. For applications where carbon dioxide is present in the sample gas, the EES retards passivation of the sensor anode by allowing the products of oxidation to dissolve in the electrolyte. In effect, the sensor is renewed continuously, resulting in an increase in sensor life even if exposed to 100% carbon dioxide. In addition, the enhanced mechanical design of the sensor ensures longer life, and virtually eliminates leakage of electrolyte, a nagging (and expensive) problem associated with sensors that require periodic electrolyte maintenance.

Specifications PERFORMANCE Measurement Ranges in Percent 0-2, 0-5, 0-10, 0-25, 0-50, and 0-100		Loop Resistance: 600 ohms @ 24 VDC (consult factory for other resistance values)	
Accuracy ¹ :	+ 1% of full scale.	SAMPLE GAS CHARACTERISTICS	
Linearity:	+ 1% of full scale.	Sample Flow Rate:	1.0 to 2.0 standard cubic feet per hour (SCFH) 0.5 to 1.0 liters/ minute (LPM)
Response Time:	90% of full scale in less than 20 seconds (typical).	Sample Gas Pressure Limits:	0.1 to 1.5 psig (0.007 to 0.1 kg/cm ²).
Sensor Type:	Long-life Electrochemical Sensor.	CONSTRUCTION	
Temperature Compensation:	Standard.	Enclosure:	Polycarbonate, rated NEMA 4X (IP66) without optional equipment. NEMA 7 (explosion proof) optional.
Operating Temperature Range:	40° to 104°F (5° to 40°C)	Dimensions:	6.5 in. (165.1 mm) height 7.0 in. (177.8 mm) width 3.9 in. (99.06 mm) depth. Note: All dimensions are without optional equipment
Warranty:	Two years for the electronics and one year for the sensor.	Gas Connections:	Quick connect 1/4" OD for plastic tubing or stainless steel compression fittings for installations with metal sample lines.
ELECTRICAL Series 2500 Loop Powered Trace Oxygen Transmitter:		Input power 14-32 VDC	
Series 2510 Trace Oxygen Transmitter:		Input power 115/230 VAC, 50-60 Hz, or 24 VDC.	
		¹ Stated at constant temperature and pressure.	



40 Albion Road, Suite 100, Lincoln, RI 02865
Tel: 401.333.8580, 800.262.5977 Fax: 401.333.5550
Email: salescontact@aoi-corp.com Web: aoi-corp.com

Alpha Omega Instruments Accepts VISA, Mastercard, and AMEX