

Model C-600A-01 Duratemp® Thermometer



FEATURES

- *Exclusive movementless design resists shock and vibration – no gears to wear or misalign resulting in increased instrument life*
- *Gas-operated molecular sieve*
- *No elevation error*
- *Mercury free*
- *One bulb size for all ranges*
- *±1% full-span accuracy*
- *Maxivision® dial*
- *Limited five-year warranty*

A high impact-resistant polished stainless steel case. Bayonet ring facilitates easy removal for glass replacement and pointer adjustment. A versatile case that enables surface or flush mounting. Available in 4½" dial size.

PRODUCT SPECIFICATIONS

Model: C-600A-01
Accuracy: ±1% of span.
Case Style: Stainless steel, bayonet ring
Dial Size: 4½" Maxivision linear anti-parallax dial black markings on a white dial
Window: Glass, shatterproof glass and plastic are optional.
Mounting and connection: Surface/Lower (C01) or Flush/Rear (C11)
Ambient Temperature: 160°F/71°C
Bulb size: 3" long by 3/8" O.D.
Bulb Material: 316 Stainless steel

- Bulb Styles:**
- 12" Bendable extension w/ ½ NPT union connection (B01)
 - Plain bulb with rigid extension no union (B03)
 - Plain bulb with rigid extension ½ NPT union on armor (B08)
 - 18" Bendable extension w/ ½ NPT union connection (B17)
 - 24" Bendable extension w/ ½ NPT union connection (B18)

Capillary Material: 300 Stainless steel
Line length: 5 – 80 in standard increments (See table 5)

Armor: AISI 302 Spring Armor standard, interlock 303 SS, PVC coated, plain and no armor are optional.

Ranges:
 –300/200°F–400/1200°F
 –200/100°C–200/650°C
 Dual scale ranges available

Over Range: 125% of span

Head/Elevation Error: None

Product Options:

Front Flange **XFF** (600A-01-C11 only)
 Dial Markings **XDM**
 Externally adjustable red set hand **XEO**
 Externally adjustable **XEP**
 Externally adjustable min. pointer **XEQ**
 Non-glare glass **XNG**
 Paper Tag **XNN**
 Stainless steel tag **XNH**
 Plastic Window **XPD**
 Shatterproof glass **XSG**
 Stationary Red Hand Set **XSH**

HOW TO ORDER

C-600A	01		C01					B01		A1		L07		AK		
	Table 1		Table 2					Table 3		Table 4		Table 5		Table 6		
	CASE STYLE		CASE STYLE		MOUNTING CONNECTION			BULB STYLES		ARMOR STYLE		LINE LENGTH		RANGES		
	CODE	DESCRIPTION	CODE	SIZE	SURFACE	FLUSH	LOWER	REAR	CODE	DESCRIPTION	CODE	DESCRIPTION	CODE	DESCRIPTION	CODE	DESCRIPTION
	01	SS Bayonet Ring	C01	4½	✓		✓		B01	12" Bendable extension with ½ NPT union connection	A1	Stainless Steel Spring	L01	5	AB	–320/200°F
			C11	4½		✓		✓	B03	Plain bulb with rigid extension, no union			L03	10	AE	–100/100°F
									B08	Plain bulb with rigid extension, ½ NPT union on armor			L07	20	AG	–40/180°F
									B17	18" Bendable extension with ½ NPT union connection			L09	30	AK	20/240°F
									B18	24" Bendable extension with ½ NPT union connection			L13	50	AL	50/300°F
									*Minimum recommended insertion length ("u" dimension) in liquids is 4 inches and in gases is 6 inches for standard ¾ x 3" bulb				L19	80	AN	50/550°F
														AR	50/750°F	
														AT	400/1200°F	
														AY	–200/100°C	
														BL	–80/40°C	
														BN	–40/80°C	
														BS	0/120°C	
														BT	10/150°C	
														BU	0/300°C	
														BW	0/400°C	
														BJ	200/650°C	
															DUAL RANGES	
														CE	0/120°C	
															20/240°F	
														CF	0/300°C	
															50/550°F	
														DR	10/150°C	
															50/300°F	
														DT	–40/80°C	
															–40/180°F	

Note: Thermowells must be used on any application where the bulb of the thermometer may be exposed to pressure, corrosive fluids, or velocity. Additionally, the use of a thermowell permits instrument interchangeability or recalibration without shutting down the process.

