



FLIR Si2-PD™

Industrial Acoustic Imaging Camera for Partial Discharge Detection



Key Features:

- Detect, locate, classify, and assess partial discharge (PD) faults from up to 200 m (656 ft) away
- Identify PD 30x smaller than ever before
- On-camera and software-based severity assessment of PD issues, and PD type classification provides best-in-class decision support
- One-handed operation with automatic tuning, 8x zoom, a 12 MP digital camera, and IP54 rating
- Made for enterprise scaling through the use of fleet management functionality so that managers can ensure the tools are being used and maintained properly

Main Applications:

- Monitor transmission & distribution conductors and components at long distances easily and reduce need for emergency repairs
- Inspect substation transformers to detect PD issues early, before they result in a dangerous and costly explosion
- Find PD issues in any piece of high-voltage equipment to reduce public complaints of radio interference and audible noise

www.flir.com/Si2-PD

SPECIFICATIONS

Acoustic Measurement	
Detection threshold	20 kHz: -7 dB SPL 35 kHz: 4 dB SPL 50 kHz: 10 dB SPL 80 kHz: 36 dB SPL 100 kHz: 51 dB SPL
Bandwidth	2-130 kHz
Directional resolution	From 1° up to 0.125°
Operating distance	From 0.3 m (1.0 ft) up to 200 m (656 ft)
Severity assessment	Automatic AI-based severity assessment including recommended actions onboard camera
Imaging & Optical	
Digital camera	12 MP color
Camera field of view	75° diagonal
Video frame rate	Camera: 60 fps / Acoustic image: 30 fps / Screen: 70 fps
Zoom	8x Digital zoom
Video image resolution	1280 × 720

User Interface	
Display	Size: 5 in. 1280 × 720 Resistive touch screen, TFT LCD, MIPI DSI
Integrated flashlight	LEDs, two modes: ON / OFF
Analysis and Reporting	
Online	FLIR Acoustic Camera Viewer (cloud service) https://acousticviewer.flir.com
Offline	FLIR Thermal Studio (desktop software)
Communication and Data Storage	
Data transfer	Wi-Fi 2.4 GHz and 5 GHz IEEE 802.11.b/g/n/ac wireless LAN USB memory stick
Camera software update	Automatic Over The Air (OTA) wireless update or via USB connection
Still image format	.nlz and .jpg
Video recording & format	Up to 5 minutes (.nlz format)
Storage, internal	128 GB (SD card)
(continued)	

For more information and to find your local support number, visit:
FLIR.com/contact/instruments-support

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact exportquestions@flir.com. ©2024 Teledyne FLIR, LLC. All rights reserved.

Revised 04/09/24
FLIR_Si2-PD_datasheet-USL-24-0111




FLIR Si2-PD™

Industrial Acoustic Imaging Camera for Partial Discharge Detection

SPECIFICATIONS, CONT.

Storage, external	USB 8 GB, Cloud storage capacity is unlimited
Image annotations	Image tags and comments
Power Supply	
Camera power input	Nominal input voltage: 12 V DC Max input: 17 V DC , 3.3 A (limited)
Battery	Li-Ion rechargeable battery pack (RRC 2054):14.4 V DC, 3.45 Ah, 49.68 Wh Usage: Up to 2.5 h (depends on ambient conditions & usage, needs to be retested and confirmed with final product) Charge time: approx. 2 h Max output: 16.8 V DC, 5 A
Battery charger	Input: 19-26 V DC, 2.8 A Max output: 17.4 V DC, 4.8 A
Environmental Data	
Operating temperature range	-10°C to 50°C (14°F to 122°F)
Storage temperature range	-20°C to 50°C max -20°C to 25°C recommended (determined by the battery)
Relative humidity	0-90% recommended
EMC	CFR47 FCC Part 15 Subpart B
Radio	CFR47 FCC Part 15 Subpart C/E, ETSI EN 301 489-1/-17, ETSI EN 300 328, ETSI EN 301 893
Ingress protection	IP54
Safety	IEC 62368-1
Declaration of conformity	See: https://support.flir.com/resources/DoC
Physical Data	
Camera size	288 mm × 182 mm × 159 mm (11 in × 7 in × 6 in)
Camera weight	~ 1.2 kg
Battery size	85 mm × 77 mm (RRC2504)
Battery weight	~ 0.25 kg
Total weight (camera + battery)	~ 1.45 kg

Specifications subject to change. For the most up-to-date specifications, please visit [flir.com](https://support.flir.com).



For more information and to find your local support number, visit:
[FLIR.com/contact/instruments-support](https://flir.com/contact/instruments-support)

Warranty and Service	
Warranty	http://www.flir.com/warranty/
Shipping Information	
Packaging, type	Cardboard box
Packaging, contents	• Camera • Battery (2 ea) • Battery charger • Power cable (4 ea) • Neck strap • Hard transport case • License card: FLIR Si-series Plugin for FLIR Thermal Studio, Perpetual license • Printed documentation • USB memory stick
Packaging, weight	6 kg (13 lb)
Packaging, size	490 mm × 365 mm × 190 mm (19.3 in × 14.4 in × 7.5 in)
EAN-13	7332558032619
UPC-12	845188029739
P/N	T912305

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact exportquestions@flir.com. ©2024 Teledyne FLIR, LLC. All rights reserved.

Revised 04/09/24
FLIR_Si2-PD_datasheet-USL-24-0111