



SITOP UPS1600/DC/24VDC/40A/IE/PN

SITOP UPS1600 40 A Ethernet/ PROFINET uninterruptible power supply with Ethernet/ PROFINET interface / OPC UA server / web server input: 24 V DC output: 24 V DC/40 A *Ex approval no longer available*

| Input | |
|---|--|
| supply voltage at DC rated value | 24 V |
| input voltage | DC 21 ... 29 V |
| adjustable response value voltage for buffer connection preset | 21.5 V |
| adjustable response value voltage for buffer connection | 21 ... 25 V; Adjustable: 21 V, 21.5 V, 22 V, 22.5 V, 23 V, 24 V, 25 V DC or via software |
| input current at rated input voltage 24 V rated value | 46 A; for max. charging current (5 A) |
| Mains buffering | |
| type of energy storage | with batteries |
| design of the mains power cut bridging-connection | Adjustable range using rotary coding switch: 0.5 min, 1 min, 2 min, 5 min, 10 min, 20 min, max. buffering time or via software |
| charging current | 0.1 A, 5 A |
| adjustable charging current maximum note | Automatically depending on battery module |
| Output | |
| output voltage | |
| • in normal operation at DC rated value | 24 V |
| • in buffering mode at DC rated value | 24 V |
| formula for output voltage | $V_{in} - \text{approx. } 0.2 \text{ V}$ |
| startup delay time typical | 60 ms |
| voltage increase time of the output voltage typical | 60 ms |
| output voltage in buffering mode at DC | 18.5 ... 27 V |
| output current | |
| • rated value | 40 A |
| • in normal operation | 0 ... 120 A |
| • in buffering mode | 0 ... 120 A |
| peak current | 120 A |
| property of the output short-circuit proof | Yes |
| design of short-circuit protection | Limitation to 3 x I rated for 30 ms/min; through-conductivity for 1.5 x I rated for 5 sec/min |
| supplied active power typical | 960 W |
| Efficiency | |
| efficiency in percent | |
| • at rated output voltage for rated value of the output current typical | 98.3 % |
| • in case of operation on rechargeable battery typical | 98.3 % |
| power loss [W] | |
| • at rated output voltage for rated value of the output current typical | 17 W |
| • in case of operation on rechargeable battery typical | 17 W |
| Protection and monitoring | |
| product function | |

- reverse polarity protection against energy storage unit polarity reversal
- reverse polarity protection against input voltage polarity reversal

Yes

Yes

Signaling

display version

- for normal operation
- in buffering mode

Normal operation: LED green (OK), floating changeover contact "Bat/OK" to setting "OK" ("OK" means: Voltage of the supplying power supply unit is greater than cut-in threshold set at the DC UPS module); Lack of buffer standby: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Battery replacement required: LED red (alarm) flashing with approx. 0.25 Hz, floating changeover contact "Alarm/Bat" switching with approx. 0.25 Hz; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed; Permissible contact current capacity: DC 60 V/1 A or AC 30 V/1 A

Buffered mode: LED yellow (Bat), floating changeover contact "OK/Bat" to setting "Bat"; Prewarning battery voltage < 20.4 VDC: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed

Interface

product component PC interface

Yes

design of the interface

Ethernet/PROFINET

Safety

galvanic isolation between input and output

No

operating resource protection class

Class III

protection class IP

IP20

Approvals

certificate of suitability

- CE marking
- UL approval
- as approval for USA
- CSA approval
- cCSAus, Class 1, Division 2
- ATEX

Yes

Yes

cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259

Yes

No

No

type of certification CB-certificate

Yes

certificate of suitability

- EAC approval
- C-Tick
- shipbuilding approval

Yes

Yes

Yes

shipbuilding approval

ABS, DNV GL

Marine classification association

- American Bureau of Shipping Europe Ltd. (ABS)
- DNV GL

Yes

Yes

EMC

standard

- for emitted interference
- for interference immunity

EN 55022 Class B

EN 61000-6-2

environmental conditions

ambient temperature

- during operation
- during transport
- during storage

-25 ... +70 °C; with natural convection

-40 ... +85 °C

-40 ... +85 °C

environmental category according to IEC 60721

Climate class 3K3, 5 ... 95% no condensation

Mechanics

type of electrical connection

- at input
- at output
- for rechargeable battery module
- for control circuit and status message

screw-type terminals

24 V DC: 2 screw terminals for 0.5 ... 16 mm²/20 ... 6 AWG

24 V DC: 2 screw terminals for 0.5 ... 16 mm²/20 ... 6 AWG

24 V DC: 2 screw terminals for 0.5 ... 16 mm²/20 ... 6 AWG

14 screw terminals for 0.2 ... 1.5 mm²/24 ... 16 AWG

width of the enclosure

70 mm

height of the enclosure

139 mm

depth of the enclosure

150 mm

required spacing

- top
- bottom

50 mm

50 mm

| | |
|---|---|
| <ul style="list-style-type: none"> • left • right | 0 mm |
| net weight | 0 mm |
| product feature of the enclosure housing can be lined up | 0.7 kg |
| fastening method | Yes |
| electrical accessories | Snaps onto DIN rail EN 60715 35x7.5/15 |
| MTBF at 40 °C | Battery module |
| reference code according to IEC 81346-2 | 318 776 h |
| other information | RB |
| | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified) |

