

product type designation

product description

Cable for IO-Link, wire end sleeves / M12

Sensor cable (4-core)

SIMATIC RF IO-Link connecting cable, pre-assembled, between IO-Link master and reader, M12 4-pole and open end, PUR, length 5 m.



suitability for use

Plug-in cable for connecting an IO-Link device to an IO-Link master

cable designation

LIY-11Y 4xAWG 22/19

wire length

5 m

electrical data

number of electrical connections

2

type of electrical connection

wire end sleeves (labeled) / M12 (female, 4 pin, straight)

loop resistance per length / maximum

108 mΩ/m

insulation resistance coefficient

20 GΩ·m

operating voltage

- maximum

30 V

mechanical data

number of electrical cores

4

design of the shield

unshielded

outer diameter

- of cable sheath

4.3 mm

material

- of the wire insulation

PVC

- of cable sheath

TPE-U Ether Isolation

color

- of the insulation of data wires

brown, white, blue, black

- of cable sheath

Black

bending radius

- with single bend / minimum permissible

34.4 mm

- with multiple bends / minimum permissible

64.5 mm

ambient conditions

ambient temperature

- during operation

-5 ... +80 °C

- during storage

-40 ... +80 °C

- during transport

-40 ... +80 °C

- during installation

-5 ... +80 °C

fire behavior

flame resistant according to AWM STYLE 21317 80°C 30V VW-1 for USA and AWM I/II A/B 80°C 30V FT-1 for Canada

product features, product functions, product components / general

product feature

- halogen-free

No

standards, specifications, approvals

UL/ETL listing / 300 V Rating

No

reference code

- according to IEC 81346-2
- according to IEC 81346-2:2019

WG
WGB

further information / internet links

internet link

- to web page: selection aid TIA Selection Tool
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAX-Download-Manager
- to website: Industry Online Support

<https://support.industry.siemens.com/cs/ww/en/view/67384964>
<http://www.siemens.com/ident/rfid>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

8/29/2023 