

PS2 keyboard 19" DE, with trackball, slide-in keyboard for devices with corresponding interface Further information, Quantity and content: see technical data



Figure similar

General information	
Product type designation	PS/2 withdrawable keyboard DEU
Control elements	
Keyboard fonts	
<ul style="list-style-type: none"> • Design • Keyboard assignment • Color of the buttons • Color of the key inscription • Key illumination • Function keys <ul style="list-style-type: none"> — Number of function keys • Number pad • status LED displays <ul style="list-style-type: none"> — for number pad — for Shift keys 	Membrane keyboard 84 (Germany (QWERTZ)) light gray dark gray No 12 Yes; Integrated into key layout Yes; Num, Caps, Scroll and Pad Yes Yes
Connection type	
<ul style="list-style-type: none"> • Bluetooth radio standard • USB • PS/2 • Cable length 	No No Yes 1.5 m
Frame size/design	
<ul style="list-style-type: none"> • Standard • 19" keyboard 	Yes; For industrial applications Yes
Installation type/mounting	
Rack mounting	Yes
Front mounting	No
Wall mounting/direct mounting	No
maximum permissible angle of inclination without external ventilation	0°
Supply voltage	
Design of the power supply	via PS/2
Input current	
Current consumption (rated value)	10 mA; Typical
Battery	
Battery-operated	No; maintenance-free
Degree and class of protection	
Splashproof	No
Standards, approvals, certificates	
CE mark	Yes

RoHS conformity	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	65 °C
Relative humidity	
• Operation, max.	80 %; no condensation
• Condensation permissible	No
Operating systems	
Runs under operating system	
• Windows CE	Yes
• Windows Vista	Yes
• Windows XP	Yes
• Windows 7	Yes
• Windows 8	Yes
connection method	
Connector type	PS/2
Mechanics/material	
Material	
• Plastic	Yes; Keyboard itself
• Sheet steel	Yes; Powder-coated drawer
Service life	
• Number of operating cycles, keys	20 000 000; Operations (approx.)
Dimensions	
Width	370 mm; Keyboard
Height	20 mm; Keyboard
Depth	138.5 mm; Keyboard
Width of the housing front	485 mm; Keyboard incl. drawer
Height of housing front	45 mm; Keyboard incl. drawer
Enclosure diameter	465 mm; Mounting depth drawer
Weights	
Weight (without packaging)	8 000 g; Without accessories
Weight (with packaging)	9 300 g
Scope of supply	
Delivery quantity in pieces	1; Keyboard incl. drawer
Other	
Merchandise	Yes
Manufacturer name	ZF Friedrichshafen AG, Cherry GmbH, Electronic Systems
Manufacturer's address	Cherrystr., 91275 Auerbach/OPf., Germany
Target devices	Suitable for IPC and HMI devices with the corresponding interfaces (see manual)
Usable in the following products	
• Product 1	6AV2124-0GC13-0AX0
• Product 2	6AV2124-0QC13-0AX0

last modified: 11/3/2021 