



DELTA connection socket Universal connection unit 2x 8-pole RJ45 Cat. 6 E  
Compact technology FLEX LSA-plus terminals Screw mounting shielded

Model		
product brand name	DELTA	
product designation	Connection socket	
design of the product	Communication	
type of composition	basic element	
General technical data		
mounting type	flush mounting	
surface processing	others	
product feature printed marking	No	
material	others	
Protection class		
protection class IP	IP20	
Suitability		
suitability for use	UAE/IAE	
Appearance		
appearance	not applicable	
color	miscellaneous	
Product details		
product feature luster terminal	No	
product feature dust cover	No	
product component		
• labeling field	No	
• hinged lid	No	
• strain relief	No	
product feature		
• halogen-free	Yes	
• transparent	No	
Mechanical Design		
height	70 mm	
depth	40 mm	
fastening method	screw mounting	
material	metal	
Approvals Certificates		
General Product Approval	other	Environment



[Miscellaneous](#)

[Confirmation](#)

[Environmental Con-  
firmations](#)

## Further information

---

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TG2026-2>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TG2026-2>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TG2026-2](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TG2026-2)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>

---

last modified:

8/1/2022 

