

680 Synergy Plus

DIGITAL WEIGHT INDICATOR



RICE LAKE
WEIGHING SYSTEMS

800-472-6703
www.ricelake.com

The Next Generation of Configurable Indicators



Rice Lake's configurable 680 Synergy Series indicator combines powerful features found in advanced instrumentation with easy-to-use functions of more basic indicators. Designed with the customer in mind, the 680 is suitable for real-world, industrial environments. Tackle general purpose weighing, straightforward automation and a wide range of applications with the 680 Synergy Series.

Powerful Functions Backed by Advanced Communication

With eight setpoints and four digital I/O, the 680 can perform basic batching and filling operations. Design a multi-step procedure and run it automatically from beginning to end with the 680's configurable batch engine. Users can also customize printed tickets with formattable gross, net, setpoint and auxiliary print formats.

The 680 also supports multiple onboard communication options, cutting costs and providing connection to multiple devices such as printers and computers.

Durable, IP69K Construction

Constructed with durable 304 stainless steel and able to withstand harsh wash-downs, the 680 maximizes process efficiency in virtually any environment or application. An IP69K rating ensures the 680 can stand up to high-pressure, high-temperature washdowns found in food processing environments.

STANDARD FEATURES

- Bright seven-digit, seven-segment LED display
- Battery backed time and date
- Full numeric keypad
- Three serial ports: two RS-232, one full duplex RS-485
- Numeric keyed entry allowed for tare and setpoint entry
- Formattable tickets
- Ethernet TCP/IP
- USB device
- Stainless steel IP69K enclosure
- Four onboard configurable digital I/O points, TTL logic

OPTIONS

- Analog output: 16-bit resolution, 0-10 VDC, 0-20 mA, 4-20 mA

SPECIFICATIONS

POWER:	Line voltages: 100-240 VAC Frequency: 50-60 Hz Power consumption: ~2W (AC) with one 350 ohm load cell, 15W max
EXCITATION VOLTAGE:	±5 VDC, 8 x 350Ω or 16 x 700Ω load cells
ANALOG OUTPUT (OPTIONAL):	Type: Voltage or current output, 16-bit resolution Voltage Output: 0-5 VDC, 0-10 VDC, +/- 5 VDC, +/- 10 VDC Voltage Load Resistance: 1KΩ minimum Current Output: 0-20 mA, 0-24 mA, 4-20 mA Current Loop Resistance: 1,000Ω maximum
ANALOG SIGNAL INPUT RANGE:	-0.5 mV/V to +7 mV/V
ANALOG SIGNAL SENSITIVITY:	1μV/graduation recommended
A/D SAMPLE RATE:	6.25-120 Hz, software selectable
RESOLUTION:	Internal: 8,000,000 counts Display: 1,000,000
SYSTEM LINEARITY / PI RATING:	Within 0.01% full scale
DIGITAL I/O:	Four configurable I/O - 5V logic
COMMUNICATION PORTS:	Two RS-232 (three-wire) RS-485 (five-wire) USB (device) Ethernet (10/100)
STATUS ANNUNCIATORS:	Eight LED annunciators
DISPLAY:	Seven 0.8 in tall, seven-segment digits
KEYS/BUTTONS:	Flat membrane panel, tactile feel (18 buttons plus ON/OFF)
TEMPERATURE RANGE:	Legal: 14°F to 104°F (-10°C to 40°C) Industrial: 14°F to 122°F (-10°C to 50°C)
DIMENSIONS (W X H X D):	11.58 in x 8.57 in x 4.05 in (29.41 cm x 21.77 cm x 10.29 cm)
WEIGHT:	6.25 lb (2.84 kg)
RATING/MATERIAL:	Rating: IP69K Material: AISI 304 Stainless Steel
WARRANTY:	Two-year limited warranty
EMC IMMUNITY:	10 V/m

APPROVALS



Measurement
Canada
Approved



Your Rice Lake Weighing Systems distributor is:

RICE LAKE
WEIGHING SYSTEMS

230 W. Coleman St. • Rice Lake, WI 54868 • USA
TEL: 715-234-9171 • FAX: 715-234-6967 • www.ricelake.com

An ISO 9001 registered company • Specifications subject to change without notice.
© 2019 Rice Lake Weighing Systems PN 196359 7/19